

## CIVIL AVIATION AUTHORITY CZECH REPUBLIC

CAA-F-ZLP-024-1-22 Flight Division

## APPLICATION AND REPORT FORM ATPL(A), MPL, training, skill test and proficiency check for Multi-pilot aeroplanes and single pilot high-performance complex aeroplanes Applicant's First and Last Name: Date of Birth: Type and No. of Licence Held: Proficiency check Type of test: Skill test: ATPL skill test: YES: NO: MPL skill test: YES: NO: SP Operation: YES: NO: П MP Operation: YES: П NO: Aircraft type: IR: YES: П NO: PBN: YES: NO: Valid till: Medical certificate (class according to the pilot licence): Class: Theoretical training for the issue of a type or class rating performed during period: **PASS FAIL** % (Pass mark 75%): From: 1 To: % Name of ATO: Name of HT: Signature of HT: (in capital letters) 2 Training on FSTD FSTD (aircraft type): Three or more axes: Yes \( \Boxed{\quad / No } \Boxed{\quad \} Ready for service and used: Visual aid: Yes ☐ / No ☐ FSTD manufacturer: Motion or system: **FSTD** operator: FSTD ID code: Instrument approaches at aerodromes to a decision altitude Total training time at the controls: or height of: Name of ATO: Location, date and time: Type rating instructor ☐ / Class rating instructor ☐ Type and number of licence (instructor): Name of instructor: Signature of instructor: (in capital letters) 3 Flight training: Aeroplane FSTD (for ZFTT) Type of aircraft: Registration: Flight time at the controls: Training aerodromes or sites: Take-offs: Landings: (take-offs, approaches and landings) Take off time: Landing time: (only for take-offs and landings training) (only for take-offs and landings training) Location and date: Name of ATO / AOC holder: Type rating instructor ☐ / Class rating instructor ☐ Type and number of licence (instructor): Name of instructor: Signature of instructor: (in capital letters)

4 Skill test / Proficiency check details:									
Type of Aeroplane and registration:						FSTD ID Code:			
Aerodrome or	Departu	Departure:		Arrival:		е:	Route:		
PASS [		FAIL _		Rea	son(s) why,	if failed:			
				·					
PARTIALLY PASSED									
Rating:	·			Original validity until:			New rating valid to:		
Provided that v Annex I (Part-l								nents of FCL.625.A IR(A) (b) & Appendix 8 to of the IR/SPA.	
Rating: IR/SP/	A/SE					New ratin	g valid to:		
I hereby declar						•	orocedures	s and requirements of the applicant's competen	
Date and locat	tion:								
Examiner's certificate number:						Type and number of licence:			
Signature of e	xamine	er:				Name in capital letters:			
5 Declaration by applicant pilot:									
I do not possess a personnel licence and rating with the same scope and in the same category issued in another Member State.									
I have not applied for a personnel licence and rating with the same scope and in the same category in another Member State. I have never held any personnel licence with the same scope and in the same category issued in another Member State which was revoked or suspended in any other Member State.  I hereby declare that all the statements in connection with this application are complete and correct. I understand that any false or misleading statement could disqualify me from being granted a personnel licence, certificate, rating, authorisation or attestation.									
Date:							Signatur	re of applicant:	

MULT	TI-PILOT AEROPLANES AND SINGLEPILOT HIGH-PERFORMANCE COMPLEX AEROPLANES	PRA	PRACTICAL TRAINING			ATPL/MPL/TYPE RATING SKILL TEST OR PROF. CHECK	
	Manouvres / Procedures	FSTD	A	Instructor initials when training completed	Tested and checked in FSTD or A	Examiner initials when test or check completed	
SECTI							
1 1.1	Flight preparation Performance calculation	OTD P					
1.2	Aeroplane external visual inspection; location of each item and purpose of inspection	OTD P#	P				
1.3	Cockpit inspection	P>	>				
1.4	Use of checklist prior to starting engines, starting procedures, radio and navigation equipment check, selection and setting of navigation and communication frequencies	P>	>		M		
1.5	Taxiing in compliance with ATC instructions or instructions of instructor	P>	>				
1.6	Before take-off checks	P>	>		M		
SECTI	ON 2						
2 2.1	Take-offs Normal take-offs with different flap settings, including expedited take-off	P>	>				
2.2*	Instrument take-off; transition to instrument flight is required during rotation or immediately after becoming airborne	P>	>				
2.3	Crosswind take-off	P>	>				
2.4	Take-off at maximum take-off mass (actual or simulated maximum take-off mass)	P>	>				
2.5 2.5.1*	Take-offs with simulated engine failure: Shortly after reaching V2	P>	>				
until rea	planes which are not certificated as transport category aching a minimum height of 500 ft above the runway ne regarding take-off mass and density altitude, the in	end. In aeropla	nes having the sa	ame performanc	e as a transport	category	
2.5.2*	between V1 and V2	P	X		M FFS only		
2.6	Rejected take-off at a reasonable speed before reaching V1	P>	>		М		
SECTI	ON 3						
3 3.1	Flight manoeuvres and procedures Manual flight with and without flight directors (no autopilot, no autothrust/autothrottle, and at different control laws, where applicable)	P>	>				
3.1.1	At different speeds (including slow flight) and altitudes within the FSTD training envelope	P>	>				
3.1.2	Steep turns using 45° bank, 180° to 360° left and right	P>	>				
3.1.3	Turns with and without spoilers	P>	>				
3.1.4	Procedural instrument flying and manoeuvring including instrument departure and arrival, and visual approach	P>	>				
3.2	Tuck under and Mach buffets (if applicable), and other specific flight characteristics of the aeroplane (e.g. Dutch Roll)	P>	An aeroplane shall not be used for this exercise		FFS only		
3.3	Normal operation of systems and controls engineer's panel (if applicable)	OTD P>	>				

MULT	TI-PILOT AEROPLANES AND SINGLEPILOT HIGH-PERFORMANCE COMPLEX AEROPLANES	PRACTICAL TRAINING			ATPL/MPL/TYPE RATING SKILL TEST OR PROF. CHECK	
	Manouvres / Procedures	FSTD	A	Instructor initials when training completed	Tested and checked in FSTD or A	Examiner initials when test or check completed
3.4	Normal and abnormal operations of following systems:				М	A mandatory minimum of 3 abnormal items shall be selected from 3.4.0 to 3.4.14 inclusive
3.4.0	Engine (if necessary propeller)	OTD P>	>			
3.4.1	Pressurisation and air conditioning	OTD P>	>			
3.4.2	Pitot/static system	OTD P>	>			
3.4.3	Fuel system	OTD P>	>			
3.4.4	Electrical system	OTD	>			
3.4.5	Hydraulic system	P> OTD	>			
3.4.6	Flight control and trim system	P> OTD	>			
3.4.7	Anti-icing/de-icing system, glare shield heating	P> OTD				
		P> OTD			M (single	
3.4.8	Autopilot/flight director  Stall warning devices or stall avoidance devices,	P> OTD			pilot only)	
	and stability augmentation devices	P>				
3.4.10	Ground proximity warning system, weather radar, radio altimeter, transponder	P>				
3.4.11	Radios, navigation equipment, instruments, FMS	OTD P>				
3.4.12	Landing gear and brake	OTD P>	>			
3.4.13	Slat and flap system	OTD	>			
3.4.14	Auxiliary power unit (APU)	OTD P>	>			
3.5	Intentionally left blank					
3.6	Abnormal and emergency procedures:				М	A mandatory minimum of 3 items shall be selected from 3.6.1 to 3.6.9 inclusive
3.6.1	Fire drills, e.g. engine, APU, cabin, cargo compartment, flight deck, wing and electrical fires including evacuation	P>	>			11101002110
3.6.2	Smoke control and removal	P>	>			
3.6.3	Engine failures, shutdown and restart at a safe height	P>	>			
3.6.4	Fuel dumping (simulated)	P>	>			
3.6.5	Wind shear at take-off/landing	P	X		FFS only	
3.6.6	Simulated cabin pressure failure/emergency descent	P>	>			
3.6.7	Incapacitation of flight crew member	P>	>			

MULTI	-PILOT AEROPLANES AND SINGLEPILOT HIGH-PERFORMANCE COMPLEX AEROPLANES	PRACTICAL TRAINING			ATPL/MPL/TYPE RATING SKILL TEST OR PROF. CHECK	
	Manouvres / Procedures	FSTD	A	Instructor initials when training completed	Tested and checked in FSTD or A	Examiner initials when test or check completed
3.6.8	Other emergency procedures as outlined in the appropriate aeroplane flight manual (AFM)	P>	>			
3.6.9	TCAS event	OTD P>	An aeroplane shall not be used		FFS only	
3.7 3.7.1	Upset recovery training Recovery from stall events in:  - take-off configuration;  - clean configuration at low altitude;  - clean configuration near maximum operating altitude; and  - landing configuration.	P FFS qualified for the training task only	X An aeroplane shall not be used for this exercise			
3.7.2	The following upset exercises:  — recovery from nose-high at various bank angles; and  — recovery from nose-low at various bank angles	P FFS qualified for the training task only	X An aeroplane shall not be used for this exercise		FFS only	
3.8	Instrument flight procedures					
3.8.1*	Adherence to departure and arrival routes and ATC instructions	P>	>		M	
3.8.2*	Holding procedures	P>	>			
3.8.3*	3D operations to DH/A of 200 ft (60 m) or to higher minima if required by the approach procedure					
	cording to the AFM, RNP APCH procedures may revaluable chosen taking into account such limitations				case of such AF	
3.8.3.1*	Manually, without flight director	P>	>		M (skill test only)	
3.8.3.2*	Manually, with flight director	P>	>			
3.8.3.3*	With autopilot	P>	>			
3.8.3.4* Manually, with one engine simulated inoperative during final approach, either until touchdown or through the complete missed approach procedure (as applicable), starting:  (i) before passing 1 000 ft above aerodrome level; and (ii) after passing 1 000 ft above aerodrome level.  In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the approach with simulated engine failure and the ensuing go-around shall be initiated in conjunction with the 2D approach in accordance with 3.8.4. The go-around shall be initiated when reaching the published obstacle clearance height/altitude (OCH/A); however, not later than reaching an MDH/A of 500 ft above the runway threshold elevation. In aeroplanes having the same performance as a transport category aeroplane regarding take-off mass and density altitude, the instructor may simulate the engine failure in accordance with exercise 3.8.3.4.		P>	>		M	
3.8.4*	2D operations down to the MDH/A	P*>	>		M	

MUL	TI-PILOT AEROPLANES AND SINGLEPILOT HIGH-PERFORMANCE COMPLEX AEROPLANES	PRACTICAL TRAINING			ATPL/MPL/TYPE RATING SKILL TEST OR PROF. CHECK	
	Manouvres / Procedures	FSTD	A	Instructor initials when training completed	Tested and checked in FSTD or A	Examiner initials when test or check completed
altitud local in flight of (b) circ centrel author Remar	Circling approach under the following cons: proach to the authorised minimum circling approach e at the aerodrome in question in accordance with the astrument approach facilities in simulated instrument conditions; followed by: cling approach to another runway at least 90° off ine from the final approach used in item (a), at the ised minimum circling approach altitude. k: If (a) and (b) are not possible due to ATC reasons, lated low visibility pattern may be performed.	P*>	>			
3.8.6	Visual approaches	P>	>			
SECT	ION 4					
4	Missed approach procedures	P*>	>			
4.1	Go-around with all engines operating* during a 3D operation on reaching decision height	P*>	>			
4.2	Go-around with all engines operating* from various stages during an instrument approach	P*>	>			
4.3	Other missed approach procedures	P*>	>			
4.4*	Manual go-around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt	P*>	>		M	
4.5	Rejected landing with all engines operating:  - from various heights below DH/MDH;  - after touchdown (baulked landing)  In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the rejected landing with all engines operating shall be initiated below MDH/A or after touchdown.	P>	>			
SECT	ION 5					
5 5.1	Landings Normal landings* with visual reference established when reaching DA/H following an instrument approach operation	P				
5.2	Landing with simulated jammed horizontal stabiliser in any out-of-trim position	P>	An aeroplane shall not be used for this exercise		FFS only	
5.3	Crosswind landings (aircraft, if practicable)	P>	>			
5.4	Traffic pattern and landing without extended or with partly extended flaps and slats	P>	>			
5.5	Landing with critical engine simulated inoperative	P>	>		M	
5.6	Landing with two engines inoperative:  - aeroplanes with three engines: the centre engine and one outboard engine as far as practicable according to data of the AFM; and - aeroplanes with four engines: two engines at one side	P	X		M FFS only (skill test only)	
Remar		•	•			

Symbols meaning: P = Trained as PIC or co-pilot and as PF and PM for the issue of a type rating as applicable. OTD = Other training devices may be used for this exercise. X = An FFS shall be used for this exercise; otherwise an aeroplane shall be used if appropriate for the manoeuvre or procedure. P# = The training shall be complemented by supervised aeroplane inspection.

The practical training shall be conducted at least at the training equipment level shown as (P), or may be conducted up to any higher equipment level shown by the arrow (---->). The following abbreviations are used to indicate the training equipment used: A = aeroplane / FFS = full-flight simulator /FSTD = flight simulator training device.

The starred items (\*) shall be flown solely by reference to instruments.

Where the letter 'M' appears in the skill test or proficiency check column, this will indicate a mandatory exercise or a choice where more than one exercise appears.

Manoeuvres and procedures shall include MCC for multi-pilot aeroplane and for single-pilot high-performance complex aeroplanes in multi-pilot operations. Manoeuvres and procedures shall be conducted in single-pilot role for single-pilot high performance complex aeroplanes in single-pilot operations.

In the case of single-pilot high-performance complex aeroplanes, when a skill test or proficiency check is performed in multi-pilot operations, the type rating shall be restricted to multi-pilot operations. If privileges of single-pilot are sought, the manoeuvres/procedures in 2.5, 3.8.3.4, 4.4, 5.5 and at least one manoeuvre/procedure from Section 3.4 have to be completed in addition as single-pilot.

In the case of a restricted type rating issued in accordance with FCL.720.A(c), applicants shall fulfil the same requirements as other applicants for the type rating except for the practical exercises relating to the take-off and landing phases.

To establish or maintain PBN privileges, one approach shall be an RNP APCH. Where an RNP APCH is not practicable, it shall be performed in an appropriately equipped FSTD.

By way of derogation from the subparagraph above, in cases where a proficiency check for revalidation of PBN privileges does not include an RNP APCH exercise, the PBN privileges of the pilot shall not include RNP APCH. The restriction shall be lifted if the pilot has completed a proficiency check including an RNP APCH exercise.

Refresher training determination for renewal of type rating	
Experience of applicant:	
Amount of time elapsed since the privileges of the rating were	last used:
Complexity of aircraft:	
Applicant has a current rating on another aircraft type or class	
Where considered necessary, the performance of the applicar or an aircraft of the relevant type or class:	nt during a simulated proficiency check for the rating in an FSTD
Determinated refresher training:	
Recommended validity of the refresher training until (date):	
This is to certify, the determinated training was successfully co	ompleted.
Name of ATO:	Approval No.:
Name of instructor:	Licence No.:
Signature of instructor:	Signature of applicant: